



ARAB PETROCHEMICAL COMPANY



ISO 9001:2000  
Certificate No.: CH98/8032

ISO 14001:2004  
Certificate No.: CH03/0112

OHSAS 18001:1999  
Certificate No.: CH05/0675

**Address:**

No. 3, Taban St.,  
Valie-e-Asr St.,  
Tehran - Iran

**Tel:**

(+98 21)82122700

**Fax:**

(+98 21)8867 4126-27

**Web-site:**

www.arpc-ir.net

**E-mail:**

Sales@arpc-ir.net

## High Density Polyethylene

### BL3

Typical properties	Test method (DIN)	Unit	Value
MFI@190°C, 5 kg	53735	gr/10min	1
Density	53479	gr/ml	0.954
Notched Impact Strength	53453	mj/mm <sup>2</sup>	≥6.5
ESCR, plax (70°C, 0.5bar)	Hoechst HDPE 19	hr	≥2
Standard Yellow Index	6167	-	≤4

> Values shown are averages & are not to be considered as product specifications.

#### ❖ Main application & Characteristics:

BL3 is a high density polyethylene grade with broad molecular weight distribution, suitable for blow moulding applications.

#### ♦ Characteristics:

- High rigidity.
- Good flow ability.
- Good impact strength.
- Good stress cracking resistance.

#### ♦ Typical applications are:

- Containers ranging from a few ml up to 10 litres.
- Sheets for thermoforming.

\* BL3 is suitable for food contact.