

攀枝花东方钛业有限公司

PANZHIHUA DONGFANG TITANIUM INDUSTRY CO., LTD.

Yizhishan Vanadium & Titanium Industrial Park, Miyi, Panzhihua City, Sichuan, P. R.China(617201)

R-5566 Technical Data Sheet

Product Characteristics

R-5566 is a rutile titanium dioxide pigment with alumina, Zirconia and organic surface treatment, with high whiteness and gloss, high scattering power, high durability and excellent dispersibility

Applications

Interior & Exterior paint, emulsion paint, powder coating, ink, paper, rubber, plastic and masterbatch

Specifications & Properties

- TiO₂ Content: 93% min
- Rutile Content: 97% min
- Inorganic Surface Treatment: Alumina, Zirconia
- Organic Treatment: Yes
- Particle Size: 0.3μ m
- Density: 4.0
- Oil Absorption: 18-23
- pH Value: 6.5~8.5

Packing

In 25kg paper bags or 500kg and 1000kg jumbo bags

Product Storage

Keep it from direct contact with moisture.

Safety Precautions

Wear gloves and safety glasses with side shields, safety shoes when handling tio₂. In case of eye contact, flush it immediately. In case of skin contact, clean it after the use.

Note: The information herein is free of charge and for the reference of trained person. Although it is believed to be reliable, it is shouldn't be considered as a warranty or to be implied in respect of such information. We strongly recommend to make experiment as appropriate before application. We don't bear any liability fr and/or in connection with use of this information.